

Budgeting and Risk Assessment for Deep Geothermal Wells

By D. LENTSCH and A. SCHUBERT*

Abstract

To date, cost planning and time schedule forecasting for the well construction process of deep geothermal wells drilled in the South German Molasse Basin have been based on a deterministic approach. This means the estimate has been based on a historic average time and uncertainties have been taken into account by adding a contingency factor. This

approach is simple and fast but it does not consider the variability of the estimate and therefore its application is limited. In this article we present an approach of probabilistic well construction modelling which can provide risk assessment for geothermal wells to investors, insurance companies and decision makers. This aids proper budgeting and the calculation of insurance premiums. Moreover, the modeled technical limit or best historic performance can be used as a technical performance reference. Probabilistic modelling also allows a sensitivity analysis to identify the key driving forces of well construction costs. Therefore, optimization

strategies can be steered into the right direction.

Introduction

Hydrothermal energy has been used in the South German Molasse Basin for decades to supply spas with warm water. However, geothermal development has also targeted district heating and power generation on a larger scale over the last ten years. Depending on the temperature and production rates, the thermal energy is used for power generation coupled with heating or, in case of lower temperatures, for heating only. A typical

* David Lentsch, Achim Schubert, ERDWERK GmbH, Munich, Germany (E-mail: Lentsch@erdwerk.com). Shortened version of a lecture presented at the conference "Celle Drilling 2013", September 9–10, 2013, Celle, Germany.




Fig. 1 Example of a probability distribution and cumulative probability of the total well construction time




Fig. 2 Drilling costs vs. Depth curve of an example well

well doublet, used for a coupled system, can support 5–50 MW for direct use (heating) and has an electrical capacity of approx. 5 MW. [1]

The geology in the South German Molasse Basin is generally well known. However, drilling down to the reservoir can be challenging and drilling performance has been unsteady in the past. To counter this, rotary steerable systems have been applied in recently drilled wells (cf. [2]) and a lot of effort has been put into well designs, which considers the lessons learned. These measures have led to a significant decrease in well delivery time and costs. However, the variability is still high and there is great potential for improved performance and saving costs.

To date, cost planning and time schedule forecasting for the well construction process have been based on historical performance data of offset wells, whereas outstandingly strong or weak performance has been rejected and an average estimated time for the main operations has been summed up to the total well delivery time. By multiplying the times with the respective costs and adding the fixed costs, total well costs have been identified. Uncertainties have been taken into account by adding a contingency factor whose value has been based on the engineer’s subjective degree of optimism.

This deterministic approach has the advantage of being simple, fast and easy to communicate. However, it does not give any idea about the uncertainty of that estimate, which limits its application: For example, the estimated time schedule was used for both, budget planning and as technical reference for the drilling contractor. But from the engineer’s point of view it was too conservative and provided no incentive for the well construction team. On the other hand, if drilling problems occurred, costs could increase rapidly and the forecast was too optimistic. Now, rather than one case, one could estimate two or more cases (e. g. best-case, business-case or worst-case) again with the same deterministic method (scenario based approach). However, it does not deliver the probability of each case and quantitative risk assessment is still not possible.

In this article we present a different approach for time and cost estimates which is based on a probabilistic well construction model. This approach allows the simulation of a time schedule forecast and the well delivery costs on a statistical basis. It allows risk assessment by yielding a distribution of expected values, the probability of a certain value and the range of outcomes.

Literature Review

In the oil & gas industry probabilistic techniques for time and cost planning of wells are well established. Its use started as an improvement on deterministic approaches by splitting up the well construction process in smaller operations, defining how their duration and costs depend on input variables and simulating an estimate for a new well by combining the operations again whilst applying actual design parameters.

For example, Thorogood [3] described “a mathematical model for analyzing drilling performance and estimating well times” in the North Sea. Shilling and Lowe [4] published a paper about the development of an “automatic cost estimating and tracking system” in the Gulf of Mexico.

Although this approach might result in a more accurate prediction it does not show the uncertainty in the planned well construction costs and time. Therefore probabilistic estimations are necessary and there are several papers on this topic: Murtha [5], Williamson et al. [6] and Akins et al. [7] refresh concisely the theoretical background of probabilistic techniques. They proposed the use of a Monte Carlo simulation for well planning and explained its strengths, weaknesses and the pitfalls. Examples for practical studies are Peterson et al. [8], Peterson et al. [9], Kitchel et al. [10], Zoller et al. [11], Hariharan et al. [12], and Adams et al. [13]. The ideas and methods described in these papers provide the theoretical basis of our work.

Methodology

The aim is to model the Total Well Construction Time of one single well and to generate

a distribution function with a Monte Carlo simulation.

Therefore the first step is to define the model. The Total Well Construction Time can be broken down into sequential steps. The processes defined are: Drilling Hole, Logging, Conditioning Tripping, Running Casing or Running Liner, Cementing, WOC/BOP and Drilling Cement/Shoe. Repeatedly connecting these seven processes for each section describes the typical well construction process without any gaps.

The process Drilling Hole is a function of following input variables:

- ROP [m/h] (Rate of penetration). ROP is measured only when the bit is rotated at bottom and mud is circulated
- DFT [h/100 m] (Drilling Flat Time). DFT is the time consumed for all operations except drilling during the drilling process, normalized to 100 m
- Casing Setting Depths and the resulting section lengths.

After defining the model it has to be fed with real values. Therefore, the duration of these processes and input variables were gathered from rig sensor records and morning reports of offset wells. Then a distribution function was assigned to every input variable by fitting a theoretical distribution to the respective data set (parametric fit). Learning trends over time were implemented by assigning a correlation coefficient between the well number and the respective input variable. Especially ROP shows a significant improvement over time. Moreover, correlations between input variables are to be considered. This means that if two variables are related to each other, the sampling of a relatively high value for one input variable should lead to a high value (or low value in case of negative correlation) for the second variable. Based on the model described above a Monte Carlo simulation can be run. Figure 1 shows the resulting probability distribution of the total well construction time of a simulated future example well.

A further step is to model drilling costs based on the time model. The total time-dependent costs can be determined by multiplying the time-dependent costs of each pro-

cess with the respective process duration. The time-independent costs are summarized and assigned to the respective section (e. g. casing, mud materials, etc.). The cost inputs can be handled either as probability distributions or fixed values depending on the phase of the project. For example, if the project is already in a phase where tender offers are available or contracts are in place, costs should be considered as fixed values.

Results

The model results can be transferred to a time vs. depth curve and cost vs. depth curve. Figure 2 shows a cost vs. depth diagram for an example well. There are six different curves on the diagram:

Firstly, the “historic technical limit”: It is the sum of the best historic process duration of all wells. Therefore, for each process (e. g. Drilling Hole), the minimum value of the offset data is gathered and stacked together. So this curve is a mixture of processes from different wells.

Then, the “best historic performance” curve is displayed, which is based on the data of the well with the best overall outcome (normalized to the modeled casing setting depths). This well does not necessarily have the best performance in all sections. Only the overall outcome was the best.

The next three curves are the modeled P10, P50 and P90 values as a function of depth. From the spread between these curves, the risk involved is indicated.

Finally, the “worst historic performance” is displayed. It is, in analogy of the “best historic performance”, based on the data of the well with the worst overall outcome (normalized to the modeled casing setting depths).

The time-independent costs of each section are displayed at the respective casing setting depths together with the time-dependent costs of the flat time processes (processes which do not add depth). The costs before spud are displayed at a depth of 0 m and represent the costs for the rig site and rig up. Then the section costs are added up until the final depth is reached. Then costs for completion and testing are added.

With the presented approach of well construction modelling, decision makers can evaluate the risk involved in the well construction process. Uncertainties are acknowledged and the variety of expected out-

comes can be communicated more effectively. The awareness of risks and opportunities is improved.

Moreover, the normalized technical limit or best historic performance can be used as a technical performance goal, which is separated from the drilling time used for budget planning. This is the foundation for performance improvement. It can also be easily assessed how good the current performance is compared to other wells. This is essential for effective performance management.

Building a probabilistic model also stimulates the analysis of offset data and the actual operational time and cost data. It also gives the opportunity to perform a sensitivity analysis. Based on the results of the sensitivity analysis, the key driving forces can be identified. Therefore, optimization strategies can be steered into the right direction.

Nomenclature

| | |
|-----|--------------------------|
| ROP | Rate of Penetration |
| DFT | Drilling Flat Time |
| FIT | Formation Integrity Test |
| BOP | Blow Out Preventer |
| WOC | Wait on Cement |

References

- [1] K. Dorsch: 10 Years of Geothermal Exploration in the South German Molasse Basin - A Summary of Where we are Today. Geothermal Energy in Bavaria (media mind), pp. 42–46, Munich, 2012.
- [2] D. Lentsch, W. Schoebel, A. Savvatis and A. Schubert: Overcoming Drilling Challenges With Rotary Steerable Technology in Deep Geothermal Wells in the Molasse Basin of Southern Germany. GRC Transactions Vol. 36, Presented at the GRC Annual Meeting, Reno, Nevada, USA, 2012.
- [3] J. L. Thorogood: A Mathematical Model for Analyzing Drilling Performance and Estimating Well Times. SPE 16524 presented at the Offshore Europe 87 conference in Aberdeen, 1987.
- [4] R. B. Shilling and D. E. Lowe: Systems for Automated Drilling AFE Cost Estimating and Tracking. SPE 20331 presented at the Fifth SPE Petroleum Computer Conference in Denver, 1990.
- [5] J. Murtha: Monte Carlo Simulation: Its Status and Future. Journal of Petroleum Technology. SPE 37932-MS, pp. 361–370, 1997.
- [6] H. S. Williamson, S. J. Sawaryn and J. W. Morrison: Some Pitfalls in Well Forecasting. SPE 89984 presented at the SPE Annual Technical Conference and Exhibition, Houston, 2004.
- [7] W. M. Akins, M. P. Abell und E. M. Diggins: Enhancing Drilling Risk and Performance Management Through the Use of Probabilistic Time and Cost Estimating. SPE 923400 presented at the SPE/IADC Drilling Conference, Amsterdam, 2005.
- [8] S. K. Peterson, J. A. Murtha and F. F. Schneider: Risk Analysis and Monte Carlo Simulaiton

Applied to the Generation of Drilling AFE Estimates. SPE 26339 presented at the SPE Annual Technical Conference, Houston, 3–6 October, 1993.

- [9] S. K. Peterson, J. A. Murtha and R. W. Roberts: Drilling Performance Predictions: Case Studies Illustrating the Use of Risk Analysis. SPE 29364 presented at the SPE/IADC Drilling Conference, Amsterdam, 28 February – 2 March, 1995.
- [10] B. G. Kitchel, S. O. Moore, W. H. Banks und B. M. Borland: Probabilistic Drilling-Cost Estimating. SPE Comp App 12, pp. 121–125, SPE 35990-PA, 1997.
- [11] S. L. Zoller, J. -R. Graulier and A. W. Paterson: How Probabilistic Methods Were Used to Generate Accurate Campaign Costs for Enterprise's Bijupir & Samelma Development. SPE 79902 presented at the SPE/IADC Drilling Conference, Amsterdam, 19–21 February, 2003.
- [12] P. R. Hariharan, R. A. Judge und D. M. Nguyen. The Use of Probabilistic Analysis for Estimating Drilling Time and Costs While Evaluating Economic Benefits of New Technologies. Paper SPE 98695 presented at the IADC/SPE Drilling conference in Miami, Florida, USA, 21–23 February, 2006.
- [13] Adams A. J. et al.: Probabilistic Well Time Estimation Revisited. SPE/IADC 119287 presented at the SPE/IADC Drilling Conference and Exhibition in Amsterdam, 2009.



David Lentsch received his M. E. Degree in Petroleum Engineering from the Mining University Leoben. Since 2009 he has been working for ERDWERK GmbH as a drilling engineer. His roles and responsibilities include mainly well engineering and well site supervision for geothermal wells. He authored and presented papers on improvement of drilling efficiency and budgeting for geothermal wells at international conferences.



Dr. Achim Schubert is a graduated geologist (PhD) and head of ERDWERK GmbH. He launched ERDWERK in 2002 after several years of professional experience in geothermal exploration and deep drilling in Germany and Austria.

His professional record covers all aspects of geothermal development from high ranking decision making down to technical problem solving. He runs the company now successfully for more than a decade with a team of recently 16 geologists and engineers and holding a wide range and network of clients and partners.